

Solid Door Reach-in Freezer Models

McCALL®



MCCF51-S

- Stainless steel doors and front shroud
- Aluminum sides
- Seamless, ABS interior liner
- Top mounted refrigeration system
- High performance refrigeration, designed to maintain -5°F to 0°F
- Ships with casters mounted from factory (2&3 section units only)
- Easy to adjust epoxy shelves (three per section)
- Easy to read digital thermometer
- 10' cord and plug attached
- Edgemount door hinges
- High density foamed in place environmentally friendly, Kyoto Protocol Compliant, Non ODP (Ozone Depletion Potential), Non GWP (Global Warming Potential) polyurethane insulation keeps energy costs low
- Environmentally friendly R404a refrigerant
- One year parts and labor, 5 year compressor warranty, limited lifetime liner warranty
- Interior accepts 18" x 26" sheet pans
- Self closing doors with stay open feature at 120°
- Low profile metal door handles



Solid Door Reach-in Freezer Models

Specifications

Model	Voltage	Amps	Storage Capacity Ft ³	Shelf Capacity Ft ²	H.P.	BTU	Ship Weight	NEMA Plug	Energy (KWH)
MCCF25-S, SH	115	9.0	20.0	15.1	1/2	1516	274lbs	5-15P	7.78
MCCF51-S, SH	115	12.0	43.5	33.2	3/4	1923	454lbs	5-15P	11.75
MCCF76-S, SH	115	20.0	66.5	48.3	1/2, 3/4	1516/1923	622lbs	14-20P	15.59

Specifications

Exterior: Top and bottom are constructed of 24-gauge galvanized steel. Exterior sides are 0.032 aluminum. Front housing is 22-gauge stainless steel.

Doors: Unit is provided with hinged solid front door(s). Door exterior is constructed of 22-gauge stainless steel. Interior door liner is formed gray ABS. Doors are provided with locks, magnetic gaskets, self-closing, edgemount hinges, and door handle(s).

Interior: Liner is constructed of seamless, one piece gray ABS material with 15 molded shelf supports spaced 3.00" (76mm) apart. Three epoxy coated wire shelves, rated at 250 lb. load capacity each, are provided per section. Liner comes with a limited lifetime warranty.

Units are completely insulated with a minimum of 2.00" (5cm) high density foamed in place environmentally friendly, Kyoto Protocol Compliant, Non ODP (Ozone Depletion Potential), Non GWP (Global Warming Potential) polyurethane.

Interior is lighted by one 40-watt incandescent light (by others) on one and two door models, and two 40-watt incandescent lights (by others) on three door models. Lights are located outside of the food zone. Door activated switches control the lights.

Refrigeration system: All components are mounted to the exterior cabinet ceiling, outside the food zone and are assembled as one piece and can be removed as one piece. Environmentally friendly R404A refrigerant is used. System has the capability of maintaining between -5°F and 0°F in heavy use food service operations. Refrigerant is metered using a highly responsive thermostatic expansion valve. On demand, evaporator defrost is automatic using a temperature initiated/temperature terminated system with electric heaters. System is controlled using an electronic temperature control, which provides improved pull down times, reducing compressor cycling and longer compressor life with lower energy consumption.

Evaporator condensate is eliminated using an energy efficient hot gas system. Temperature is displayed with exterior digital thermometer.

Others: Unit is supplied standard with a 10' cord and plug, attached. 4" diameter casters with an overall height of 5" are mounted on the unit from the factory on self-contained models (2&3 section units only).

McCall reserves the right to make changes to the design or specifications without prior notice.

